










ENERGISING THE FUTURE...

SS34572MC

345wp



-  Excellent Power Output with +ve Tolerance upto **4.99Wp**
-  **12 Years** Limited Product Warranty
-  **25 Years** of Linear Power Guarantee
-  Online **EL** Testing (Pre & Post Lamination) for ensuring defect free modules
-  All products are **PID**, Ammonia & Salt mist corrosion resistant
-  Excellent performance at low **Light** condition
-  Excellent **Temperature** coefficients and performance

- The panels are constructed with Anti Reflective Coating (ARC) toughened low iron, textured high light transmission glass
- Multi layer composite Film and Ultra Fast Cure EVA.
- Reinforced anodized Aluminum Frame with Twin Wall Profile
- Pre-drilled frame for easy mounting
- IP68 rated Junction Box connector
- Solar MC4 compatible connector



APPLICATION

CONSTRUCTIONAL CHARACTERISTICS

CERTIFICATION

- On-grid system
- BIPV
- Solar Farms
- Standalone (off-grid) Systems
- Battery charging
- Solar Water Pumping

- Glass
- EVA
- Cells
- EVA
- Back Sheet
- Frame

- IEC 61215:2005/IS 14286:2010
- IS/IEC 61730:2004 Part I & II
- IEC 62804 (PID)
- IEC 62716
- IEC 61701



SS34572MC

345wp

SPECIFICATIONS	SS34572MC
	Multi Crystalline Solar Cell
Electrical Characteristics	
Open Circuit Voltage (Voc)	46.60 V
Optimum Operating Voltage (Vmp)	37.25 V
Short Circuit Current (Isc)	9.56 A
Optimum Operating Current (Imp)	9.27 A
Power at STC (Pmax)	345 W
Module Efficiency (η) %	17.34%
Operating Conditions	-40°C to +85°C at 85% RH
Maximum System Voltage	1500 VDC
NOCT	45°C ± 2°C
Mechanical Characteristics	
Weight	21.8Kg
Module Dimension (L) X (W) X (D)	1985 x 1002 x 40 ± 1mm
Mounting Hole (Oblong)	8 X 10±0.5 mm
Mounting Hole CTC distance - vertical	1176 ± 1 mm
Mounting Hole from corner (h)	404.5 ± 1 mm
Mounting Hole CTC distance - horizontal	953±1mm

